



Norsafe A Parts List			
POS	QTY	DESCRIPTION	MATERIAL
1	8	WINDOW	Stalinite
2	1	TOP HATCH	Aluminium
3	1	FORWARD HATCH	GRP
4	3	UNDER PRESSURE RELEASE VALVE	GRP/Brass
5	2	BOBBIN	Galv.steel
6	1	KEEL SHOE	Galv.steel
7	1	STEERING NOZZLE	GRP
8	1	BOLLARD	ANSI 316L
9	1	SPRINKLER SYSTEM	Aluminium
10	1	PAINTER RELEASE	Galv.steel
11	4	SIDE HATCHES	GRP
12	1	FENDER	Rubber
13	2	AFT HATCHES	GRP
14	1	POSITION INDICATING LIGHT	
15	2	LIFE LINE	Plastic plating Steel
16	2	SKATE ARRANGEMENT	
17	1	RADAR REFLECTOR BRACKET	ANSI 316L
18	1	RADAR REFLECTOR	
19	1	42 V POWER SUPPLY	
20	1	STERN GLAND	BRASS
21	2	WINCH WIRE PENETRATION	
22	1	RAIN COLLECTOR SYSTEM	
23	1	ROPE LADDER	

**MAIN DIMENSIONS & SPECIFICATION**

LENGTH WITH FENDER:	12,02 m
LENGTH OVER ALL:	11,95 m
BREADTH WITH FENDER:	4,01 m
BREADTH OVER ALL:	3,95 m
HEIGHT OVER ALL:	3,96 m
DEPTH:	1,43 m
HOOK HEIGHT ABOVE KEEL:	2,40 m
HOOK DISTANCE:	11,20 m
WEIGHT FULLY EQUIPPED:	APPROX. 10225 Kg
DAVIT LOAD 150 PERSONS @82,5 KG:	22600 Kg
SPEED:	MIN 6 Knots

**NOTES:**

- Due to manufacturing reasons, dimensions may vary up to 50mm.
- Port side lifeboat shown.

0	Issued for construction	KARL	PHLI	THWA	30.05.2019.
REV	DESCRIPTION	BY	CHECK	APPRO	DATE
REVISION HISTORY					
		VIKING Norsafe Life-Saving Equipment Norway AS P.O Box 115 Tel: +47 37 05 85 00 4852 Færvik Fax: +47 37 05 85 01 NORWAY 24/7 Service: +47 37 05 63 33 Email: viking@viking-life.com			
		This drawing is the sole property of VIKING Norsafe Life-Saving Equipment Norway AS. It must not be submitted to other parties nor used in any manner detrimental to our interests. It shall not be copied, reproduced, used for manufacturing or sale without the written consent of VIKING Norsafe Life-Saving Equipment Norway AS. All rights are reserved.			
DWG SIZE: A3	SCALE:	COPY OF:	PART NO.	WEIGHT:	SHEET 1 / 1
CLIENT NO:	PROJECTION METHOD	EXTERNAL GA			
TOLERANCES: ISO 2768-mk, ISO 13920-BF	REVISION: 0	NADIRO DIB 125			
DWG No: G-503252	PROJECT:	MAXIMA-120 DC			
		GENERAL ARRANGEMENT			